



Zep, Inc.
1310 Seaboard Industrial Blvd
Atlanta, GA 30318
1-877-4-BUY-ZEP (428-9937)
www.zep.com

Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name ZEP 40
Product use Aerosol Cleaner
Product code 0144
Date of issue 07/21/08 **Supersedes** 06/28/05

Emergency Telephone Numbers

For MSDS Information:
Compliance Services 1-877-4-BUY-ZEP (428-9937)

For Medical Emergency
(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By
Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Printing date: 03/09/10

Section 2. Hazards Identification

Emergency overview

WARNING !

CAUSES EYE IRRITATION.

CONTENTS UNDER PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry Dermal contact. Inhalation.

Eyes

Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin

May cause skin irritation. Product may be dermal absorbed. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation

Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation.

Ingestion

May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Prolonged or repeated contact may dry skin and cause irritation. Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, eyes, central nervous system (CNS), ears.

Carcinogenicity

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Product/ingredient name **ACGIH** **IARC** **EPA** **NIOSH** **NTP** **OSHA**
None.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
ETHANOL; ethyl alcohol; grain alcohol	64-17-5	10 - 20
HYDROCARBON PROPELLANT; blend of propane & isobutane	75-28-5; 74-98-6	5 - 15
ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	1 - 5
ISOPROPYL ALCOHOL; ipa; dimethylcarbinol; 2-propanol	67-63-0	<3

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact Flush affected skin with plenty of water. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

*Hazard Determination System (HDS): Health, Flammability, Reactivity

1	1	0
---	---	---

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point Closed cup: 28.3°C (83°F)

Flammable Limits Not available.

Flammability Non-flammable. (CSMA Method)

Fire hazard In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Fire-Fighting Procedures Use an extinguishing agent suitable for the surrounding fire. Cool closed containers exposed to fire with water. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Observe label precautions. Wash contaminated clothing before reusing. Wash thoroughly after handling.

Storage CONTENTS UNDER PRESSURE. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Product name

ETHANOL; ethyl alcohol; grain alcohol

HYDROCARBON PROPELLANT; blend of propane & isobutane

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butyoxyethanol; butyl cellosolve

ISOPROPYL ALCOHOL; ipa; dimethylcarbinol; 2-propanol

Exposure limits

ACGIH TLV / OSHA PEL (United States).

TWA: 1000 ppm 8 hour(s).

ACGIH TLV / OSHA PEL (United States). Notes: Propane

TWA: 1000 ppm 8 hour(s).

ACGIH TLV (United States).

TWA: 20 ppm 8 hour(s). Form:

OSHA PEL (United States). Skin

TWA: 50 ppm 8 hour(s). Form:

ACGIH TLV (United States).

TWA: 200 ppm 8 hour(s).

OSHA PEL (United States).

TWA: 400 ppm 8 hour(s).

ACGIH/OSHA (United States).

STEL: 400 ppm 15 minute(s).

Personal Protective Equipment (PPE)

Eyes Safety glasses.

Body For prolonged or repeated handling, use gloves. Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.



Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.]

pH 10.5 - 11.0

Boiling Point 93°C (199.4°F)

Specific Gravity 1.1

Solubility Easily soluble in the following materials: cold water and hot water.

Color Clear. Colorless.

Odor Alcohol-like. [Slight]

Vapor Pressure Not determined.

Vapor Density Not determined.

Evaporation Rate 1 (Water = 1)

VOC (Consumer) 300 g/l (27.33%)

Section 10. Stability and Reactivity**Stability and Reactivity**

The product is stable.

Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LD50 Oral	Rat	7060 mg/kg	-
	LC50 Inhalation Vapor	Rat	20000 mg/m ³	4 hours
Ethylene Glycol Monobutyl Ether	LD50 Dermal	Rabbit	680 mg/kg	-
	LD50 Oral	Rat	1746 mg/kg	-
	LC50 Inhalation Vapor	Rat	450 ppm	4 hours
	LD50 Dermal	Rabbit	13000 mg/kg	-
Isopropyl Alcohol	LD50 Oral	Rat	4700 mg/kg	-
	LC50 Inhalation Vapor	Rat	22500 ppm	8 hours
	LC50 Inhalation Vapor	Rat	19000 ppm	8 hours

Section 12. Ecological Information**Environmental Effects**

Not available.


Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification		Consumer commodity	ORM-D		
IMDG Class	1950	Aerosols, non-flammable (Propellant; Blend of Isobutane, Propane and n-Butane)	2.2		

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

United States inventory (TSCA 8b): Not determined.

State Regulations

California Prop 65 No products were found.

Product code 0144

Material Safety Data Sheet

Product Name ZEP 40

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.*