



# MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2006  
Page 1 of 14

Union Carbide urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and fire prevention, as necessary or appropriate to use and understand the data contained in this MSDS.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors and others whom it knows or believes will use this material of the information in this MSDS and any other information regarding hazards or safety; 2) Furnish this same information to each of its customers for the product; and 3) Request its customers to notify their employees, customers, and other users of the product of this information.

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### 1.1 IDENTIFICATION

Product Name	GoldCoat #330 Oil Seal
Chemical Name	Not applicable
Chemical Family	Vinyl Acrylic Latex
Formula	Not applicable
Synonym	Not applicable

### 1.2 COMPANY IDENTIFICATION

Union Carbide Corporation  
A Subsidiary of The Dow Chemical Company  
39 Old Ridgebury Road  
Danbury, CT 06817-0001

### 1.3 EMERGENCY TELEPHONE NUMBER

24 hours a day: CHEMTREC 1-800-424-9300.  
Number for non-emergency questions concerning MSDS (732) 563-5522  
Additional information on this product may be obtained by calling: (919)469-6785.

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 2 of 14

### 2. COMPOSITION INFORMATION

Component	CAS #	Amount (%W/W)
Vinyl acetate, butyl acrylate polymer	25067-01-0	< 55%
Water	7732-18-5	45 %
Vinyl acetate	108-05-4	0.1 %
Acetaldehyde	75-07-0	0.04 %

### 3. HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

Appearance White

Physical State Liquid

Odor Mild

Hazards of product WARNING! VAPOR MAY BE HARMFUL IF INHALED.  
MAY CAUSE SKIN IRRITATION.

#### 3.2 POTENTIAL HEALTH EFFECTS

##### Effects of Single Acute Overexposure

**Inhalation** May cause irritation of the respiratory tract, experienced as burning sensation of eyes, nose, and throat, sneezing, coughing, and nausea.

**Eye Contact** Liquid may cause discomfort in the eye with slight excess redness and possibly swelling of the conjunctiva.

**Skin Contact** Brief contact is not irritating. Prolonged contact, as from clothing wet with the material, may cause mild irritation, experienced as discomfort, and seen as local redness.

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 3 of 14

---

**Skin Absorption** No evidence of harmful effects from available information.

**Swallowing** No evidence of harmful effects from available information.

### Chronic, Prolonged or Repeated Overexposure

**Effects of Repeated Overexposure** No adverse effects anticipated from available information.

**Other Effects of Overexposure** None currently known.

### Medical Conditions Aggravated by Exposure

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

### **3.3 POTENTIAL ENVIRONMENTAL EFFECTS**

See Section 12 for Ecological Information.

## **4. FIRST AID PROCEDURES**

### **4.1 INHALATION**

Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given by qualified personnel if necessary. Call a physician.

### **4.2 EYE CONTACT**

Immediately flush eyes with water and continue washing for several minutes. Remove contact lenses, if worn. Obtain medical attention

### **4.3 SKIN CONTACT**

Remove contaminated clothing. Wash skin with soap and water. If irritation persists or if contact has been prolonged, obtain medical attention.

### **4.4 SWALLOWING**

No harmful effects expected.

### **4.5 NOTES TO PHYSICIAN**

Toxicology studies have shown similar material to be of very low acute toxicity. There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 4 of 14

---

### 5. FIRE FIGHTING MEASURES

#### 5.1 FLAMMABLE PROPERTIES

Flash Point - Closed Cup: *Not applicable.*

Flash Point - Open Cup: *Not applicable.*

Autoignition Temperature: *Not currently available.*

#### Flammable Limits In Air:

Lower *Not Determined, Aqueous System*

Upper *Not Determined, Aqueous System*

#### 5.2 EXTINGUISHING MEDIA

Non-flammable (aqueous solution): After water evaporates, remaining material will burn. Apply alcohol-type or all-purpose-type foam by manufacturers' recommended techniques for large fires. Use water spray, carbon dioxide or dry chemical media for small fires.

#### 5.3 EXTINGUISHING MEDIA TO AVOID

No information currently available.

#### 5.4 SPECIAL FIRE FIGHTING PROCEDURES

No information currently available.

#### 5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Use self-contained breathing apparatus when fighting fires in enclosed areas.

#### 5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS

Product will not burn but may spatter if temperature exceeds boiling point of water.

#### 5.7 HAZARDOUS COMBUSTION PRODUCTS

Burning can produce the following products: Carbon monoxide and carbon dioxide. Carbon monoxide is highly toxic if inhaled. Carbon dioxide in sufficient concentrations can act as an asphyxiant.

### 6. ACCIDENTAL RELEASE MEASURES

**Steps to be Taken if Material is Released or Spilled:**

## MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
**Page** 5 of 14

Small spills can be flushed with large amounts of water; larger spills should be collected for disposal.

**Personal Precautions:** Wear suitable protective equipment. See Section 8.2 - Personal Protection.

**Environmental Precautions:** Not toxic to fish or plants.

### 7. HANDLING AND STORAGE

#### 7.1 HANDLING

##### **General Handling**

Avoid breathing vapor from container opening.  
Avoid contact with skin and clothing.  
Keep container closed.  
Use with adequate ventilation.  
Wash thoroughly after handling.

FOR INDUSTRY USE ONLY.

##### **Ventilation**

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

#### 7.2 STORAGE

Store above 4 °C (40 °F). Do not freeze.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### 8.1 EXPOSURE LIMITS

Component	Exposure Limits	Skin Form
Vinyl acetate	10 ppm TWA8 ACGIH 35 mg/m <sup>3</sup> TWA8 ACGIH 15 ppm STEL ACGIH 53 mg/m <sup>3</sup> STEL ACGIH	
Vinyl acetate	10 ppm TWA8 OSHA-Vacated	

## MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
**Page** 6 of 14

---

	30 mg/m <sup>3</sup> TWA8 OSHA-Vacated
	20 ppm STEL OSHA-Vacated
	60 mg/m <sup>3</sup> STEL OSHA-Vacated
Vinyl acetate	5 ppm TWA8 UCC
Vinyl acetate	15 ppm STEL UCC
Acetaldehyde	25 ppm CEILING ACGIH
	45 mg/m <sup>3</sup> CEILING ACGIH
Acetaldehyde	180 mg/m <sup>3</sup> TWA8 OSHA-Vacated
	150 ppm STEL OSHA-Vacated
	270 mg/m <sup>3</sup> STEL OSHA-Vacated
	100 ppm TWA8 OSHA-Vacated
	200 ppm TWA8 OSHA
	360 mg/m <sup>3</sup> TWA8 OSHA

*In the Exposure Limits Chart above, if there is no specific qualifier (i.e., Aerosol) listed in the Form Column for a particular limit, the listed limit includes all airborne forms of the substance that can be inhaled.*

*A "Yes" in the Skin Column indicates a potential significant contribution to overall exposure by the cutaneous (skin) route, including mucous membranes and the eyes, either by contact with vapors or by direct skin contact with the substance. A "Blank" in the Skin Column indicates that exposure by the cutaneous (skin) route is not a potential significant contributor to overall exposure.*

---

### 8.2 PERSONAL PROTECTION

<b>Respiratory Protection:</b>	None required if airborne concentrations are maintained below listed exposure limits. If airborne concentrations exceed listed exposure limits, select respiratory protection equipment in accordance with OSHA Standard 29 CFR 1910.134. If necessary, use NIOSH approved mist respirator in poorly ventilated areas.
<b>Ventilation:</b>	General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.
<b>Eye Protection:</b>	Safety glasses or monogoggles, as appropriate
<b>Protective Gloves:</b>	Polyvinyl chloride coated

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 7 of 14

### 8.3 ENGINEERING CONTROLS

Avoid inhalation of product spray through the use of engineering controls. General (mechanical) room ventilation is expected to be satisfactory. Use local exhaust if needed to control mist or vapor.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Appearance: White

pH: 5 Approx.

Solubility in Water (by weight): Completely miscible

Odor: Mild

Boiling Point (760 mmHg): ~ 100 °C ~ 212 °F

Freezing Point: 0 °C 32 °F

Specific Gravity (H<sub>2</sub>O = 1): 1.1

Vapor Pressure at 20°C: 2.4 kPa 18 mmHg

Vapor Density (air = 1): 0.6

Evaporation Rate (Butyl Acetate = 1): 0.8

Dynamic Viscosity: 500 cps Approx.

Melting Point: *Not applicable.*

## 10. STABILITY AND REACTIVITY

10.1 STABILITY/INSTABILITY Stable

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 8 of 14

---

**10.2 HAZARDOUS POLYMERIZATION** Will Not Occur.

**10.3 INHIBITORS/STABILIZERS** Not applicable.

### **11. TOXICOLOGICAL INFORMATION**

Information on analogous products shows minimal toxicity concerns.

#### **ACUTE TOXICITY**

##### **Peroral**

Rat; LD50 = > 2000 mg/kg

##### **Percutaneous**

Rat; LD50 = > 2000 mg/kg

#### **SIGNIFICANT DATA WITH POSSIBLE RELEVANCE TO HUMANS**

Vinyl Acetate is identified by IARC as a potential carcinogen. This product may contain small amounts of vinyl acetate. Lifetime exposure to high vapor concentrations (600 ppm) of Vinyl Acetate caused malignant and benign tumors of the respiratory tract of rats, but not mice; this response possibly being associated with the irritant effect. Vinyl acetate has been tested for carcinogenic potential in rats in two separate drinking water studies. In one study in which animals were exposed to concentrations up to 0.5% in water, there was no evidence of carcinogenicity. In the second study, conducted at higher concentrations (up to 1% in water), evidence of cancer in the stomach and oral cavities was observed. There is no evidence that vinyl acetate has caused cancer in humans. There should be minimal risk when used with ventilation adequate to keep the atmospheric concentration of Vinyl Acetate below the recommended exposure limit. Male rats receiving Vinyl Acetate at high concentrations in drinking water (0.5%) for two generations possibly demonstrated a decreased ability to produce offspring.

# MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 9 of 14

## 12. ECOLOGICAL INFORMATION

### 12.1 ENVIRONMENTAL FATE

Not toxic to fish or plants. Does not inhibit bacteria in waste treatment facilities. Polymer is not biodegradable. Product is not RCRA hazardous. The following information is based on analogy with a similar material.

**BOD (% Oxygen consumption)**

	Day 5	Day 10	Day 15	Day 20	Day 30
				1 - 8 %	

### 12.2 ECOTOXICITY

**Toxicity to Micro-organisms**

IC50

Result value: > 2000 mg/l

**Toxicity to Aquatic Invertebrates**

Daphnia; EC50

Result value: > 1000 mg/l

**Toxicity to Fish**

Fathead Minnow; LC50

Result value: > 1000 mg/l

### 12.3 FURTHER INFORMATION

None.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 WASTE DISPOSAL METHOD

Incinerate in a furnace or otherwise dispose of in accordance with applicable Federal, State and local requirements. Dispose in accordance with all applicable Federal, State, and local

## MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
**Page** 10 of 14

environmental regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

### **13.2 DISPOSAL CONSIDERATIONS**

Does not inhibit bacteria in waste treatment facilities. Polymer is not biodegradable. Product is not RCRA hazardous. See Section 13.1

*Disposal methods identified are for the product as sold. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permissible under applicable rules, regulations and/or laws governing your location.*

## **14. TRANSPORT INFORMATION**

### **14.1 U.S. D.O.T.**

#### **NON-BULK**

**Proper Shipping Name :** NOT REGULATED

#### **BULK**

**Proper Shipping Name :** NOT REGULATED

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

## **15. REGULATORY INFORMATION**

### **15.1 FEDERAL/NATIONAL**

#### **COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 SECTION 103 (CERCLA)**

The following components of this product are specifically listed as hazardous substances in 40 CFR 302.4 (unlisted hazardous substances are not identified) and are present at levels which could require reporting:

# MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
Page 11 of 14

---

None.

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EPCRA) SECTIONS 302 AND 304

The following components of this product are listed as extremely hazardous substances in 40 CFR Part 355 and are present at levels which could require reporting and emergency planning:

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
Vinyl acetate	108-05-4	<= 0.1000%

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EPCRA) SECTION 313

The following components of this product are listed as toxic chemicals in 40 CFR 372.65 and are present at levels which could require reporting and customer notification under Section 313 and 40 CFR Part 372:

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
Vinyl acetate	108-05-4	<= 0.1000%

---

## SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EPCRA) SECTIONS 311 AND 312

**Delayed Hazard :** Yes  
**Fire Hazard :** No  
**Immediate Health Hazard :** No  
**Reactive Hazard :** No  
**Sudden Release of Pressure Hazard :** No

## TOXIC SUBSTANCES CONTROL ACT (TSCA)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

---

## CEPA - DOMESTIC SUBSTANCES LIST (DSL)

The components of this product are on the DSL or are exempt from reporting under the New Substances Notification Regulations.

---

## MATERIAL SAFETY DATA SHEET

Product Name: GoldCoat #330 Oil Seal  
MSDS#: 1945

Effective Date: 06/27/2000  
Page 12 of 14

---

### 15.2 STATE/LOCAL

#### PENNSYLVANIA (WORKER AND COMMUNITY RIGHT-TO-KNOW ACT)

This product is subject to the Worker and Community Right-to-Know Act. The following components of this product are at levels which could require identification in the MSDS:  
None.

---

#### MASSACHUSETTS (HAZARDOUS SUBSTANCES DISCLOSURE BY EMPLOYERS)

The following components of this product appear on the Massachusetts Substance List and are present at levels which could require identification in the MSDS:

Component	CAS #	Amount
Vinyl acetate	108-05-4	<= 0.1000%
Acetaldehyde	75-07-0	<= 0.0400%

---

#### CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986)

This product contains the following chemical(s) known to the State of California to cause cancer:

Component	CAS #	Amount
Acetaldehyde	75-07-0	<= 0.0400%

---

#### CALIFORNIA SCAQMD RULE 443.1 (SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT RULE 443.1, LABELING OF MATERIALS CONTAINING ORGANIC SOLVENTS)

VOC: Not applicable.

---

*This section provides selected regulatory information on this product including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.*

### 16. OTHER INFORMATION

# MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
**Page** 13 of 14

---

## 16.1 AVAILABLE LITERATURE AND BROCHURES

Additional information on this product may be obtained by calling: (919)469-6785.

## 16.2 SPECIFIC HAZARD RATING SYSTEM

Additional information on this product may be obtained by calling: (919)469-6785.

## 16.3 RECOMMENDED USES AND RESTRICTIONS

FOR INDUSTRY USE ONLY

## 16.4 REVISION

Version: 3.

Revision: 06/27/2000

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

## 16.5 LEGEND

A	Asphyxiant
Bacterial/NA	Non Acclimated Bacteria
F	Fire
H	Health
HMIS	Hazardous Materials Information System
N/A	Not available
NFPA	National Fire Protection Association
O	Oxidizer
P	Peroxide Former
R	Reactivity
TS	Trade Secret
VOL/VOL	Volume/Volume
W	Water Reactive
WW	Weight/Weight

*The opinions expressed herein are those of qualified experts within Union Carbide. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of the use of the product are not under the*

## MATERIAL SAFETY DATA SHEET

**Product Name:** GoldCoat #330 Oil Seal  
**MSDS#:** 1945

**Effective Date:** 06/27/2000  
**Page** 14 of 14

---

*control of Union Carbide, it is the user's obligation to determine conditions of safe use of the product.*